KOSMEX CO., LTD

TRUSTABLE & DEDICATED

Bed slats

Contact infomation

Email: anna@kosmexgroup.com
Whatsapp: +84-399-741-589
Website: www.kosmexgroup.com

Specification

- **Standard sizes**

15 x 60 x 680-1180mm or customerized sizes

- **Thickness tolerant**:

+/-1mm

- **Surface:** Rubber face
- **Core veneer:** Rubber hardwood
- **Edge: sanded**
- **Glue:** MR glue Class 1 | EN 636:2003
- **Wood material**

Legally Source Plantation Wood

- **Density**


Rubber: 700-720kg/m3

- **Formaldehyde Emission** Standard E0/E1/E2
- **Moisture Content**

8-12%

About us

Kosmex offers strong bed slats, can bear weight 70kgs up



Dimensional deviation as per EN 315 and EN 324

Length/Width	*Deviation*
<1000 mm	*±1mm*
1000-2000mm	*±1mm*
>2000mm	*±1mm*

Skills & Experience

- **Knowledge of Wood Selection: Understanding how to choose the right types of wood for making strong, durable plywood. Use dry machine to dry veneer, ensure veneer get good moisture content**
- **Plywood Manufacturing Process: Experience in the steps of making plywood, including cutting, drying, gluing, and pressing layers together.**
- **Focus on Sustainability: Using eco-friendly practices, like sourcing wood responsibly and choosing safer materials.**
- **Quality Control: Ensuring the plywood meets high standards by testing for strength, flexibility, and overall durability.**