KOSMEX CO., LTD

TRUSTABLE & DEDICATED

Upholstery Plywood

Contact infomation

Email: anna@kosmexgroup.com
Whatsapp: +84-399-741-589
Website: www.kosmexgroup.com


Specification

- **Standard sizes:** 1220x2440mm
- **Thickness tolerant**: +/-0.5mm
- **Thickness:** 12mm
- **Surface:** Pine
- **Grade:** CP/CP
- **Core veneer:** Eucalyptus
- **Layer thickness**: 1.6mm
- **Glue: MR**
- **Formandehyde emission:** E0.5
- **Density: 630-650 Kg/m3**
- **Core gaps:** Have
- **Overlap:** Have

- **Moisture Content**
  8-12%

About us

Kosmex offers a plywood with high density & strong plywood, guarantee cutting no delamination



Dimensional deviation as per EN 315 and EN 324

Length/Width	*Deviation*
<1000 mm	*±1mm*
1000-2000mm	*±1mm*
>2000mm	*±1mm*

Skills & Experience

- **Knowledge of Wood Selection: Understanding how to choose the right types of wood for making strong, durable plywood. Use dry machine to dry veneer, ensure veneer get good moisture content**
- **Plywood Manufacturing Process: Experience in the steps of making plywood, including cutting, drying, gluing, and pressing layers together.**
- **Focus on Sustainability: Using eco-friendly practices, like sourcing wood responsibly and choosing safer materials.**
- **Quality Control: Ensuring the plywood meets high standards by testing for strength, flexibility, and overall durability.**